HALE TRAILER BRAKE & WHEEL

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	800-232-6535
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com • follow us online @haletrailer

800-232-6535 *FINANCING AVAILABLE

FONTAINE Specialized

A042374

VIN: A8120

Traverse TA (Model: TRV4053TA)	
TTA4053F*843492GV	Est. Wt.: TBD# +/- 3%
TRAILER - GENERAL	
Capacity: 40 tons distributed evenly: 25 tons in 10 feet: GAWR and tire ratings determine legal loads.	
Load Base: 10-foot rigid 2-point load centered in deck.	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with minimum 50,000# webs.	
Length: 52 feet 10 inches - 43 feet KP to CL of Rear Axle.	
Width: 102 inches.	
GOOSENECK	
Gooseneck Design: Fixed full width with slope	
Gooseneck Platform: Full width gooseneck platform with 1 3/8-inch wood floor.	
Loaded Fifth Wheel Height: 48 inches.	
Swing Radius: 81 inches.	
Power Source: Setup for wet line operation	
Winch: 20K Braden Winch, located at front of gooseneck with 100 feet of cable	
Winch Guard: None standard	
Manual Controls: RS only for Winch, GN cylinders, Travel Cylinders.	
Radio Remote Control: 3 functions, 6 buttons.	
Landing Gear: 2-speed OEM Standard with road-side crank handle.	
Toolboxes: (2) side-opening toolboxes (1 on each side of GN)	
Electrical Receptacle: J560 7-pin connector.	
DECK	
Deck Design: Flat level deck design.	
Deck Length: 43 feet 1 inch clear deck length.	
Loaded Deck Height: 37 inches with 14 inches ground clearance at GN.	
Flooring: 1 3/8-inch nominal wood (full width).	
Crossmembers: 8-inch centers.	
Loading Angle: 6.5 degrees.	
Unloading Angle: 15 degrees.	
Tie Downs: Chain slots on deck siderails on 16-inch centers. Four-way key-hole slots down the center of the main deck on 16-inch centers.	
Deck to Bogie Connection: Dual acting tandem slide hydraulic cylinders with combination roller and slide pads.	
AXLES	
Number of Axles: 2.	
Axle Capacity: 25,000 lb. nominal capacity per axle. NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Brakes: 12.25 inches x 7.5 inches with 6-inch autoslacks - heavy duty brake drums - outboard mount.	
Axle Spread: 49 inches (between axles).	
Spring Brakes: Spring brakes (2 axles).	
SUSPENSION	
Suspension: Air ride with automatic height controls.	
ABS: 4S/2M system without diagnostic tool and cable.	
Air Weigh Scale: Air Weigh Scale installed	
WHEELS AND TIRES	
Wheels: 6.75 x 17.5 Outer Aluminum/Inner Steel	
Tires: 235/75R 17.5 H-ply Economical OEM Standard	
Tire Inflation System: Tire Inflation System installed	

LIGHTING

Electrical System: DOT sealed beam and harness with LED lights.	
Marker Lights: 3 marker lights per side including mid-turn (24 total).	
Auxiliary Electrical Connection: 4 Pin socket on curb-side rear of deck.	
LED Work Lights: LED work lights on gooseneck drop	
Electrical Receptacle: J560 7-pin connector	
PAINT	
Paint: GALVANIZED	
)	
MISCELLANEOUS	
Bumper: FMVSS compliant with 3 lights per side and 3 center lights.	
Access Steps: Steps installed on RS & CS of GN.	
Central Greasing System: Greasing system for all bogie-mounted greasing locations included.	
VIN Plate: Bilingual VIN plate.	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.